

HTA-AH15

4 IN 1 Metal bullet Camera



PRODUCT DESCRIPTION

4 in 1 camera feature

- Support AHD, TVI, CVI, CVBS signal free switching;
- 8 million progressive scan CMOS for jagged-free motion image capture
- Support AHD/TVI/CVI coaxial high-definition
- output for clear and delicate images.
- Illumination, 0.1 Lux@(F1.2,AGC ON), 0 Lux with IR
- Support IR-CUT switch, CDS external control, day and night monitoring.
- Supports OSD menu control for user-defined settings.
- Supports digital wide dynamic
- Adaptive Digital Noise Reduction, 3D-DNR, 2D-DNR
- Supports coaxial video control (UTC) function
- Video 6KV lightning protection, power supply large capacitor design
- Applicable scenarios: scenic spots, underground parking lots, supermarkets, etc.



Camera	Image Sensor	18.0"3/M GC5053 CMOS Sensor
	Minimum Illumination	0.1Lux@(F1.2,AGC ON), 0LUX with IR
	Video Output Mode	4 IN 1 AHD/CVI/TVI/CVBS (default TVI)
	Image Resolution	2560 (H) × 1920 (V)
	Effective Pixels	1920P@20fps /12.5fps,1080P@25fps/30fps
	TV System	PAL/NTSC
	Coaxial audio output	Support
	Focal Length:	3.6mm (5MP,M12 ports)
	Night vision distance	2PCS Warm leds,IR distance1015-M;
	S/N Ratio	≥50dB
Camera Features	Starlight	/
	Day/Night	YES
	OSD Menu Language	Default English
	White Balance	AUTO / MANUAL
	Gain Control	AUTO
	Noise Reduction	DNR
	DWDR	YES
	OSD Support	/ (Optional)
	UTC	/ (Optional)
	Dip Switch	/
General	Housing	Metal, IP66
	Bracket	YES
	Heater	NO
	Audio	/
	Working Temperature & humidity	-20° ~ +60° RH95% Max
	Power Source	DC12V/2A±10%;
	Dimension	Ø110mm*66mm
	Weight	500g

Usine : Section 214 - LOT 7 , Zone Industrielle Sidi Bel-Abbes - Algérie.

المصنع: القسمة 214-ملكية رقم 7, المنطقة الصناعية بلدية سيدي بلعباس - الجزائر.

+213 (0) 48 77 00 01 / +213 (0) 48 77 07 32

+213 (0) 48 77 00 10

info@hta-dz.com

